

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

WHAT IS CLAIMED IS:

Sub. a1 >

1. A system for exchanging heat with a fluid, for heating the fluid comprising:

a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein;

a fluid inlet, for enabling the fluid to flow into the heat exchanger; and

a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger.

2. The system of claim 1, wherein the heat exchanger comprises a storing element for storing heat, and a heating element for heating the storing element.

3. The system of claim 1, wherein the heat exchanger is comprised of aluminum.

4. The system of claim 1, further comprising a sealing element for sealing the heat exchanger.

5. The system of claim 1, wherein the fluid inlet comprises an inlet valve.

6. The system of claim 1, wherein the fluid outlet comprises an outlet valve.

7. The system of claim 1, further comprising a sensing element for sensing the temperature of the heat exchanger, and for controlling and stabilizing the temperature thereof.

Sub. A1 >

8. The system of claim 1, further comprising a system for dispensing the fluid, which includes the heat exchanger therein.

9. The system of claim 1, wherein the heat exchanger is further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanger evaporates through the fluid outlet responsive thereto.

10. The system of claim 1, further comprising a flow-controlling element for controlling the flow of the fluid from the fluid outlet for dispensing thereof.

11. The system of claim 1, further comprising an operation-controlling element for controlling the operation of the system.

12. The system of claim 2, wherein the storing element is adapted to enable the fluid to be in direct contact therewith.

13. The system of claim 2, wherein the storing element is further adapted to maintain the fluid at a heated fluid temperature, and to enable the fluid to be heated thereabove substantially rapidly to a fluid dispensing temperature.

14. The system of claim 2, wherein the heating element is generally m-shaped.

15. The system of claim 2, wherein the heating element is adapted to be connected to a heating source.

16. The system of claim 2, wherein the channel is generally spiral-shaped.

Sub. 21

17. The system of claim 8, wherein the heat exchanger is located generally in the upper portion of the fluid dispensing system.

18. The system of claim 8, wherein the fluid dispensing system further includes an outlet for dispensing the heated fluid.

19. The system of claim 10, wherein the flow-controlling element comprises a flowmeter.

20. The system of claim 11, wherein the operation-controlling element comprises a processing element for processing the temperature of the heat exchanger.

21. The system of claim 18, wherein the fluid dispensing outlet comprises a fluid spray head.

22. The system of claim 20, wherein the processing element comprises a microprocessor.

23. A system for exchanging heat with a fluid, for heating the fluid comprising:

a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein;

a fluid inlet, for enabling the fluid to flow into the heat exchanger; and
a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger;
wherein the heat exchanger is further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanger evaporates through the fluid outlet responsive thereto.

Rule 1126
Sub. A1 >

24
25. A system for exchanging heat with a fluid, for heating the fluid comprising:

a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, wherein the heat exchanger comprises a storing element for storing heat, and a heating element for heating the storing element, and the heating element is generally m-shaped;

10 a fluid inlet, for enabling the fluid to flow into the heat exchanger; and
a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger.

25
26. A system for exchanging heat with a fluid, for heating the fluid, comprising:

a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, wherein the heat exchanger has a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, and the channel is generally spiral-shaped;

10 a fluid inlet, for enabling the fluid to flow into the heat exchanger; and
a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger.

26
27. A system for exchanging heat with a fluid, for heating the fluid, comprising:

means for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein;

Sub. A1

a fluid inlet, for enabling the fluid to flow into the heat exchanging means,
and
a fluid outlet, for enabling the heated fluid to flow out of the heat exchanging
10 means.

²⁷
28. The system of claim ²⁶27, wherein the heat exchanging means are further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanging means evaporates through the fluid outlet responsive thereto.

²⁸
29. The system of claim ²⁶27, wherein the heat exchanging means comprise a storing element for storing heating, and a heating element for heating the storing element, and the heating element is generally m-shaped.

²⁹
30. The system of claim ²⁶27, wherein the heat exchanging means have a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, and the channel is generally spiral-shaped.

³⁰
31. A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to
5 enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, a fluid inlet, for enabling the fluid to flow into the heat exchanger, and a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger, wherein the method comprises:
enabling fluid to flow through the fluid inlet into the heat exchanger;
10 exchanging heat with the fluid in the heat exchanger so as to heat the fluid and store heat energy; and

Sub. A17

enabling heated fluid to flow out of the heat exchanger and through the fluid outlet.

³¹
~~32.~~ The method of claim ~~31~~³⁰, wherein the heat exchanger comprises a storing element for storing heat, and a heating element for heating the storing element, and wherein exchanging heat comprises heating the storing element and storing heat.

³²
~~33.~~ The method of claim ~~31~~³⁰, wherein the heat exchanger is comprised of aluminum, and wherein exchanging heat comprises exchanging heat with the fluid in the aluminum heat exchanging means.

³³
~~34.~~ The method of claim ~~31~~³⁰, further comprising a sealing element for sealing the heat exchanger, further comprising sealing the heat exchanger.

³⁴
~~35.~~ The method of claim ~~31~~³⁰, wherein the fluid inlet comprises an inlet valve, and wherein enabling fluid inlet flow comprises enabling the fluid to flow through the inlet valve.

³⁵
~~36.~~ The method of claim ~~31~~³⁰, wherein the fluid outlet flow comprises an outlet valve, and wherein enabling fluid outlet flow comprises enabling the fluid to flow through the outlet valve.

³⁶
~~37.~~ The method of claim ~~31~~³⁰, further comprising a sensing element for sensing the temperature of the heat exchanger and for controlling and stabilizing the temperature thereof, further comprising sensing the temperature of the heat exchanger and controlling and stabilizing the temperature thereof.

Sub. 217

³⁷
38. The method of claim ³⁰31, further comprising a system for dispensing the fluid, which includes the heat exchanger therein, further comprising dispensing the fluid from the fluid dispensing system.

³⁸
39. The method of claim ³⁰31, wherein the heat exchanger is further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanger evaporates through the fluid outlet responsive thereto, further comprising evaporating any fluid remaining in the heat exchanger, after dispensing fluid, responsive to the retained heat in the heat exchanger.

³⁹
40. The method of claim ³⁰31, further comprising a flow-controlling element for controlling the flow of the fluid from the fluid outlet for dispensing thereof, further comprising controlling the flow of the fluid from the fluid outlet for dispensing thereof.

⁴⁰
41. The method of claim ³⁰31, further comprising an operation-controlling element for controlling the operation of the system, further comprising controlling the operation of the system.

⁴¹
42. The method of claim ³¹32, wherein the storing element is adapted to enable the fluid to be in direct contact therewith, and wherein exchanging heat comprises enabling fluid to be in direct contact with the storing element.

⁴²
43. The method of claim ³¹32, wherein the storing element is further adapted to maintain the fluid at a heated fluid temperature, and to enable the fluid to be heated thereabove substantially rapidly to a fluid dispensing temperature, and wherein exchanging heat comprises maintaining the fluid at a heated fluid temperature and enabling the fluid to be substantially rapidly heated thereabove to a fluid dispensing temperature.

Sub. A1> 44.⁴³ The method of claim 32,³¹ wherein the heating element is generally m-shaped, and wherein exchanging heat further comprises heating the storing element through the generally m-shaped heating element.

45.⁴⁴ The method of claim 32,³¹ wherein the heating element is adapted to be connected to a power source, and wherein exchanging heat further comprises heating the heating element upon actuating the power source.

46.⁴⁵ The method of claim 32,³² wherein the channel is generally spiral-shaped, and wherein exchanging heat further comprises enabling fluid to flow into the generally spiral-shaped channel.

47.⁴⁶ The method of claim 38,³⁷ wherein the heat exchanger is located generally in the upper portion of the fluid dispensing system, and wherein exchanging heat further comprises exchanging heat in the generally upper portion of the fluid dispensing system.

48.⁴⁷ The method of claim 38,³⁷ wherein the fluid dispensing system further includes an outlet for dispensing the heated fluid, and wherein dispensing further comprises dispensing the fluid from the heated fluid dispensing outlet.

49.⁴⁸ The method of claim 40,³⁹ wherein the flow-controlling element comprises a flowmeter, and wherein controlling further comprises controlling the flow of the fluid in the flowmeter.

50.⁴⁹ The method of claim 41,⁴⁰ wherein the operation-controlling element comprises a processing element for processing the temperature of the heat exchanger, and wherein operation-controlling further comprises processing the temperature of the heat exchanger.

Sub. A1 >

51. The method of claim ~~47~~⁵⁰, wherein the fluid dispensing outlet comprises a fluid spray head, and wherein dispensing further comprises dispensing through the fluid spray head.

52. The method of claim ~~50~~⁵¹, wherein the processing element comprises a microprocessor, and wherein sensing further comprises processing through a microprocessor.

53. A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, a fluid inlet, for enabling the fluid to flow into the heat exchanger, and a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger, wherein the heat exchanger is further adapted to retain heat, such that, upon turning off the fluid inlet, after dispensing fluid, any fluid remaining in the heat exchanger evaporates through the fluid outlet responsive thereto, and wherein the method comprises:

enabling fluid to flow through the fluid inlet into the heat exchanger;

exchanging heat with the fluid in the heat exchanger so as to heat the fluid and store heat energy;

enabling heated fluid to flow out of the heat exchanger and through the fluid outlet;

turning off the fluid inlet;

dispensing fluid; and

evaporating any fluid remaining in the heat exchanger through the fluid outlet, responsive to the retained heat in the heat exchanger.

Sub. 217 54

54. A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, wherein the heat exchanger comprises a storing element for storing heat, and a heating element for heating the storing element, which is generally m-shaped, a fluid inlet, for enabling the fluid to flow into the heat exchanger, and a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger, wherein the method comprises:

- enabling fluid to flow through the fluid inlet into the heat exchanger;
- exchanging heat with the fluid through the generally m-shaped heating element in the heat exchanger, so as to heat the fluid and store heat energy; and
- enabling heated fluid to flow out of the heat exchanger and through the fluid outlet.

54
55

55. A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, wherein the channel is generally spiral-shaped, a fluid inlet, for enabling the fluid to flow into the heat exchanger, and a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger, wherein the method comprises:

- enabling fluid to flow through the fluid inlet into the generally spiral-shaped channel in the heat exchanger;
- exchanging heat with the fluid in the generally spiral channel in the heat exchanger so as to heat the fluid and store heat energy; and
- enabling heated fluid to flow out of the generally spiral-shaped channel in the heat exchanger and through the fluid outlet.

Sub. 217

56. A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises means for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, a fluid inlet, for enabling the fluid to flow into the heat exchanging means, and a fluid outlet, for enabling the heated fluid to flow out of the heat exchanging means, wherein the method comprises:

- 10 enabling fluid to flow through the fluid inlet into the heat exchanging means; exchanging heat with the fluid in the heat exchanging means so as to heat the fluid and store heat energy; and enabling heated fluid to flow out of the heat exchanging means and through the fluid outlet.

57. The method of claim 56, wherein the heat exchanger is further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanging means evaporates through the fluid outlet responsive thereto, further comprising evaporating any fluid remaining in the heat exchanging means, after dispensing of the fluid, responsive to the retained heat in the heat exchanging means.

58. The method of claim 56, wherein the heat exchanging means comprise means for storing heat, and means for heating the storing means, and the heating means are generally m-shaped, and wherein exchanging heat comprises heating the storing means through the generally m-shaped heating means and storing heat in the storing means.

59. The method of claim 56, wherein the heat exchanging means have a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, and the channel is generally spiral-

Sub. A) shaped, and wherein exchanging heat comprises enabling fluid to flow into the
5 generally spiral-shaped channel in the heat-exchanging means and enabling fluid
to be retained in the heat exchanging means.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000